

- All-season Performance tire designed for SUV or light trucks
- Directional high-void pattern designed for excellent all-season traction
- Jointless spiral-wound cap ply maximizes ride refinement and durability
- Overall construction designed to improve lateral stability and handling on SUV/LT vehicles
- Unique sidewall construction designed to strike an optimal balance between cornering performance and ride refinement
- M&S All-season rated
- UTQG 360 A A
H — speed rating
- UTQG 360 A B
S — speed rating



Part #	Tire Size	Service Description / Ply Rating	Side wall	Overall Diameter (in)	Section Width (in)	Rim Width (in)	Tread Depth (in)	Max Load (lbs)	Max PSI
TP18432000	P235/60R14	96H	BSW	25.1	9.4	7.0	10/32	1565	44
TP39214000	P205/70R15	96H	BSW	26.3	8.3	6.0	11/32	1565	36
TP25712200	P225/70R15	100H	BSW	27.4	8.9	6.5	12/32	1764	36
TP39428000	P235/60R15	98H	BSW	26.1	9.4	7.0	10/32	1653	44
TP27042400	P235/70R15	103H	BSW	28.0	9.4	7.0	12/32	1929	36
TP27027600	P235/75R15	105H	BSW	28.9	9.4	6.5	12/32	2039	36
TP39429400	P245/60R15	101H	BSW	26.6	9.7	7.0	11/32	1819	44
TP39462000	P255/60R15	102H	BSW	27.1	10.2	7.5	11/32	1874	44
TP23880000	P265/50R15	99H	BSW	25.5	10.8	8.5	11/32	1720	44
TP39244200	P265/70R15	112S	BSW	29.6	10.7	8.0	12/32	2469	36
TP39472000	P275/60R15	107H	BSW	28.0	11.0	8.0	11/32	2149	44
TP23858000	P295/50R15	108H	BSW	26.6	12.3	9.5	11/32	2205	44
TP40972000	P215/65R16	98H	BSW	27.0	8.7	6.5	10/32	1653	36
TP41062000	P215/70R16	100H	BSW	27.9	8.7	6.5	11/32	1764	36
TP41018200	P225/70R16	102H	BSW	28.4	9.0	6.5	12/32	1874	36
TP41008400	P235/60R16	100H	BSW	27.1	9.4	7.0	10/32	1764	44
TP41082400	P235/70R16	105H	BSW	29.0	9.5	7.0	12/32	2039	36
TP41102400	P245/70R16	107H	BSW	29.5	9.8	7.0	12/32	2149	36
TP41222000	P255/65R16	109H	BSW	29.1	10.2	7.5	10/32	2271	36
TP41026000	P255/70R16	111H	BSW	30.1	10.4	7.5	12/32	2403	36
TP41105100	P265/70R16	112S	BSW	30.6	10.7	8.0	12/32	2469	36
TP41112000	P275/60R16	109H	BSW	29.0	11.0	8.0	11/32	2271	44
TP41108200	P275/70R16	114S	BSW	31.2	11.1	8.0	12/32	2601	35
TP42403000	225/55R17	97H	BSW	26.8	9.1	7.0	11/32	1609	44
TP42403400	P225/55R17	97V	BSW	26.8	9.1	7.0	11/32	1609	44
TP42442000	235/65R17	104H	BSW	29.1	9.5	7.0	10/32	1984	44
TP42030000	P255/55R17	102H	BSW	28.0	10.4	8.0	11/32	1874	44
TP41452000	P255/60R17	106H	BSW	29.1	10.0	7.5	11/32	2094	44
TP41308200	P265/70R17	115S	BSW	31.7	10.8	8.0	12/32	2679	36
TP42044000	P275/55R17	109H	BSW	28.9	11.0	8.5	11/32	2271	44
TP42406000	P275/60R17	110H	BSW	29.9	11.1	8.0	11/32	2337	44
TP41502000	P285/60R17	114H	BSW	30.6	11.3	8.5	11/32	2601	44
TP43110000	P255/55R18	105H	BSW	29.0	10.3	8.0	11/32	2039	44
TP43162000	P265/60R18	109H	BSW	30.5	10.5	8.0	11/32	2271	44
TP43190000	P285/50R18	109H	BSW	29.2	11.7	9.0	11/32	2271	44
TP43182000	P285/55R18	113H	BSW	30.0	11.5	9.0	11/32	2535	44
TP43200000	P285/60R18	116H	BSW	31.5	11.4	8.5	11/32	2756	44



- All-season Performance tire designed for SUV or light truck enthusiasts
- Directional high-void pattern designed for excellent all-season traction
- Jointless spiral-wound cap ply maximizes ride refinement and durability
- Solid center rib offers extra stability and confidence at higher speeds
- Overall construction designed to improve lateral stability and handling on SUV/LT vehicles
- Unique sidewall construction designed to improve steering precision, response and ride refinement
- Pronounced rim protector built to protect your wheels from curb damage
- M&S All-season rated
- UTQG 360 A A

Part #	Tire Size	Service Description / Ply Rating	Side wall	Overall Diameter (in)	Section Width (in)	Rim Width (in)	Tread Depth (in)	Max Load (lbs)	Max PSI
TP00001100	205/70R15	96H	BSW	26.4	8.1	6.0	11/32	1565	36
TP25725000	225/70R15	100H	BSW	27.4	8.9	6.5	12/32	1764	36
TP50393000	225/75R15	102H	BSW	28.3	8.9	6.0	12/32	1874	36
TP42445000	235/70R15	103H	BSW	28.0	9.4	7.0	12/32	1929	36
TP00003100	215/65R16	102H XL	BSW	27.0	8.7	6.5	10/32	1874	50
TP00004100	215/70R16	100H	BSW	27.9	8.7	6.5	11/32	1764	36
TP00027100	225/70R16	107H XL	BSW	28.4	9.0	6.5	12/32	2149	42
TP00006100	235/60R16	104H XL	BSW	27.2	9.4	7.0	10/32	1985	50
TP00019100	245/70R16	111H XL	BSW	29.5	9.4	7.0	12/32	2403	42
TP41226000	255/65R16	109H	BSW	29.1	10.2	6.5	10/32	2265	44
TP00022100	265/70R16	112H	BSW	30.6	10.7	8.0	12/32	2469	36
TP42443200	235/65R17	108V XL	BSW	29.0	9.4	7.0	10/32	2205	50
TP00179100	255/60R17	110H XL	BSW	29.1	10.1	7.5	11/32	2337	50
TP00258100	255/65R17	110H	BSW	30.1	10.1	7.5	10/32	2337	44
TP00159100	265/65R17	112H	BSW	30.6	10.7	8.0	10/32	2469	44
TP00017100	275/55R17	109V	BSW	28.9	10.9	8.5	11/32	2271	44
TP43150000	235/55R18	104V	BSW	28.3	9.5	7.5	11/32	1764	44
TP00166100	235/60R18	107V XL	BSW	29.1	9.4	7.0	10/32	2149	50
TP43117200	255/55R18	109V XL	BSW	29.1	10.3	8.0	11/32	2271	50
TP43250000	265/60R18	110H	BSW	30.5	10.7	8.0	11/32	2337	44
TP00061100	255/50R19	107V XL	BSW	29.1	10.3	8.0	11/32	2150	50
TP00062100	285/45R19	111V XL	BSW	28.9	11.3	9.5	11/32	2403	50
TP00338100	245/40ZR20	99W XL	BSW	27.7	9.8	8.5	11/32	1709	50
TP00306100	245/45ZR20	99W	BSW	28.7	9.6	8.0	11/32	1709	44
TP43155200	255/45R20	105V XL	BSW	29.0	10.1	8.5	11/32	2039	50
TP45302000	265/50R20	112V XL	BSW	30.4	10.9	8.5	12/32	2469	50
TP00141100	275/40R20	106W XL	BSW	28.7	10.8	9.5	11/32	2094	50
TP00469100	275/45R20	111V XL	BSW	29.7	10.6	9.0	11/32	2403	50
TP45316000	275/55R20	117V XL	BSW	32.0	11.1	8.5	11/32	2833	50
TP45320200	285/50R20	112V	BSW	31.2	11.6	9.0	12/32	2469	44
TP45204200	295/40R20	110V XL	BSW	29.1	11.8	10.5	12/32	2337	50
TP45201000	295/45R20	114V XL	BSW	30.4	11.7	10.0	11/32	2601	50
TP45418000	305/50R20	116V	BSW	32.0	12.4	9.5	12/32	2756	44
TP00140100	265/40R22	106V XL	BSW	30.4	10.7	9.5	11/32	2094	50
TP45405000	305/40R22	114V XL	BSW	31.6	12.2	11.0	10/32	2601	50
TP45415000	305/45R22	118V XL	BSW	32.8	11.9	10.0	12/32	2910	50
TP00422100	295/35R24	110V XL	BSW	32.1	11.9	10.5	11/32	2335	50
TP00158100	305/35R24	114V XL	BSW	32.4	12.3	11.0	11/32	2601	50
TP00172100	305/30R26	111V XL	BSW	33.2	12.5	11.0	11/32	2403	50

BSW - Black Sidewall

OWL - Outline White Letter

OBL - Outline Black Letter

XL - Extra Load

Sizes may be limited by market.

- Optimal tread design for decreased tread squirm and better handling
- Four U-shaped circumferential grooves designed for excellent hydroplaning resistance
- Multi-pitch tread block design minimizes tread pattern noise
- Jointless spiral-wrapped fully nylon cap ply for added strength and durability
- Special tread compound formulated for outstanding comfort, mileage and wet/dry traction
- M&S All-season rated
- UTQG BSW 420 A A
OWL 420 A B
(Metric sizes only)



Part #	Tire Size	Service Description / Ply Rating	Side wall	Overall Diameter (in)	Section Width (in)	Rim Width (in)	Tread Depth (in)	Max Load (lbs)	Max PSI
TP00524100	205/70R15	96H	BSW	28.0	9.4	6.5	11/32	1565	44
TP15807000	215/70R15	98S	OWL	26.9	8.7	6.5	11/32	1653	44
TP25900000	225/70R15	100S	OWL	27.5	9.5	6.5	11/32	1764	44
TP42445500	235/70R15	103S	OWL	28.0	9.4	6.5	11/32	1929	44
TP39234600	255/70R15	108S	OWL	29.1	10.4	7.5	12/32	2205	44
TP39249500	265/70R15	112S	OWL	29.7	10.9	8.0	12/32	2469	44
TP00211100	215/65R16	98H	BSW	27.0	8.5	6.5	11/32	1653	44
TP00396100	215/70R16	100H	BSW	28.0	8.5	6.5	11/32	1764	44
TP00400100	235/60R16	100V	BSW	27.2	9.1	7.0	9/32	1764	44
TP00398300	235/70R16	109V	BSW	28.0	9.4	6.5	11/32	2265	44
TP00398100	235/70R16	106H	BSW	29.1	9.3	7.0	11/32	2095	44
TP41109000	245/70R16	107S	OWL	29.6	10.0	7.0	12/32	2149	44
TP41106800	265/70R16	112S	OWL	30.6	10.7	8.0	12/32	2469	44
TP00395100	225/65R17	102H	BSW	28.7	8.3	6.5	9/32	1875	44
TP00458100	235/60R17	102H	BSW	27.1	9.4	7.0	11/32	1875	44
TP00455100	235/65R17	104V	BSW	29.1	9.3	7.0	10/32	1985	44
TP00401100	255/60R17	110H XL	BSW	29.1	9.8	7.5	10/32	2335	50
TP39628800	235/50R18	101V XL	BSW	27.3	9.3	7.5	10/32	1819	50
TP00290100	235/55R18	99V	BSW	28.3	9.4	7.5	11/32	1708	44
TP00459100	235/60R18	103H	BSW	27.1	9.4	7.0	11/32	1929	44
TP00393100	255/55R18	109V XL	BSW	29.1	10.2	8.0	10/32	2265	50
TP43252000	265/60R18	110S	OWL	30.5	10.7	8.0	10/32	2335	44
TL18528400	30X9.50R15LT	104S 6	OWL	29.3	9.8	7.5	14/32	1985	50
TL18529800	31X10.50R15LT	109S 6	OWL	30.3	10.7	8.5	14/32	2270	50



- Double steel-belted construction for long-lasting wear and uniformity
- Jointless spiral-wrapped full nylon cap for added strength and durability
- All-season tread pattern delivers a smooth, quiet ride for light truck and sport utility vehicles
- Specially formulated rubber compound allows for exceptional handling in various road and weather conditions
- M&S All-season rated
- UTQG 480 A B (P-metric sizes only)

Part #	Tire Size	Service Description / Ply Rating	Side wall	Overall Diameter (in)	Section Width (in)	Rim Width (in)	Tread Depth (in)	Max Load (lbs)	Max PSI
TP26055000	P225/70R14	98S	OWL	26.6	9.2	6.5	12/32	1675	35
TP18434000	P235/60R14	96S	OWL	25.1	9.4	7.0	10/32	1565	44
TP39202400	205/70R15	99S	BSW	26.3	8.1	6.0	11/32	1709	49
TP25713000	P225/70R15	100S	OWL	27.6	9.3	6.5	12/32	1753	35
TP27050000	P225/75R15	102S	OWL	28.3	9.1	6.0	13/32	1874	35
TP27042100	P235/70R15	103S	OWL	28.1	9.7	7.0	12/32	1929	41
TP27034000	P235/75R15	105S	OWL	29.0	9.4	6.5	13/32	2038	35
TP27043000	P245/70R15	105S	OWL	28.7	10.0	7.0	13/32	2028	35
TP39230000	P255/70R15	108S	OWL	29.3	10.6	7.5	13/32	2183	35
TP39432000	P275/60R15	107S	OWL	28.0	11.0	8.0	11/32	2149	44
TP23860000	P295/50R15	108S	OWL	26.6	12.3	9.5	11/32	2205	44
TP41072000	P215/70R16	99S	OWL	28.0	8.7	6.5	12/32	1709	35
TP41018000	P225/70R16	101S	OWL	28.6	9.2	6.5	12/32	1819	41
TP41019000	P225/75R16	104S	OWL	29.4	9.0	6.0	13/32	1984	35
TP41080600	P235/70R16	106S	OWL	29.1	9.7	7.0	12/32	2039	41
TP41086000	P235/75R16	108S	OWL	30.0	9.5	6.5	13/32	2205	36
TP41101800	P245/70R16	107S	OWL	29.7	10.0	7.0	13/32	2149	41
TP41200000	P245/75R16	109S	OWL	30.6	10.0	7.0	13/32	2271	35
TP41224000	255/65R16	109T	OWL	29.1	10.2	7.5	11/32	2271	44
TP41103100	P265/70R16	112S	OWL	30.8	11.0	8.0	13/32	2469	41
TP41150000	P265/75R16	114S	OWL	31.7	10.8	7.5	14/32	2601	35
TP41122000	P285/60R16	111S	OWL	29.4	11.5	8.5	11/32	2403	44
TP39670000	P295/50R16	107S	OWL	27.6	12.1	9.5	11/32	2149	44
TP25715600	225/65R17	102S	BSW	28.5	9.1	6.5	10/32	1874	44
TP42448000	235/65R17	104H	BSW	29.1	9.5	7.0	10/32	1984	44
TP41140000	P245/65R17	107S	OWL	29.5	9.8	7.0	10/32	2149	44
TP41292000	P265/65R17	112S	BSW	30.6	10.6	8.0	11/32	2469	44
TP41304200	P265/70R17	115S	OWL	31.8	10.8	8.0	13/32	2535	35
TP42412000	P275/60R17	110S	OWL	30.0	11.0	8.0	11/32	2337	44
TP42416000	P275/65R17	115S	OWL	31.1	10.9	8.0	11/32	2679	44
TP43022000	P235/55R18	99V	BSW	28.3	9.4	7.5	11/32	1708	44
TP43208000	P285/60R18	116H	BSW	31.5	11.5	8.5	11/32	2756	44
TL15904200	LT215/75R15	100/97S 6	BSW	27.7	8.5	6.0	13/32	S1765/D1609	50
TL30166200	LT215/85R16	115/112Q 10	BSW	30.4	8.7	6.0	13/32	S2680/D2470	80
TL30174700	LT225/75R16	110/107S 8	OWL	29.4	8.8	6.0	13/32	S2335/D2150	65
TL30174200	LT225/75R16	115/112Q 10	OWL	29.4	9.0	6.0	13/32	S2680/D2470	80
TL30183400	LT235/85R16	120/116Q 10	BSW	31.7	9.4	6.5	15/32	S3042/D2778	80
TL30203200	LT245/75R16	120/116Q 10	OWL	30.6	10.1	7.0	13/32	S3042/D2778	80
TL30213600	LT265/75R16	112/109Q 6	OWL	31.7	10.8	7.5	14/32	S2470/D2270	50
TL30213800	LT265/75R16	123/120M 10	OWL	31.7	10.8	7.5	14/32	S3415/D3085	80
TL30265000	LT285/75R16	122/119Q 8	OWL	32.9	11.7	8.0	14/32	S3305/D3000	65
TL37307000	LT265/70R17	118/115Q 8	OWL	31.8	10.8	8.0	13/32	S2910/D2680	65
TL18541000	31X10.50R15LT	109S 6	OWL	30.3	10.9	8.5	15/32	2270	50
TL15811000	215/70R15C	106/104R 6	BSW	26.9	8.7	6.5	11/32	S2094/D1984	54

BSW - Black Sidewall

OWL - Outline White Letter

OBL - Outline Black Letter

XL - Extra Load

Sizes may be limited by market.

- Double steel-belted construction for long-lasting wear and uniformity
- Jointless spiral-wrapped full nylon cap for added strength and durability
- All-season tread pattern delivers a smooth, quiet ride for light truck and sport utility vehicles
- Specially formulated rubber compound allows for exceptional handling in various road and weather conditions
- Two polyester body plies absorb road shock for a smooth and comfortable ride
- M&S All-season rated
- UTQG 540 A B (P-metric sizes only)



Part #	Tire Size	Service Description /Ply Rating	Side wall	Overall Diameter (in)	Section Width (in)	Rim Width (in)	Tread Depth (in)	Max Load (lbs)	Max PSI
TP18436000	P235/60R14	96S	OWL	25.1	9.5	7.0	10/32	1565	44
TP25800000	P245/60R14	98S	OWL	25.6	9.8	7.0	11/32	1675	44
TP25721000	P225/70R15	100S	OWL	27.6	9.3	6.5	12/32	1753	35
TP27042900	P235/70R15	102S	OWL	28.1	9.8	7.0	12/32	1896	35
TP27034300	P235/75R15	105S	OWL	28.9	9.5	6.5	13/32	2028	35
TP39234000	P255/70R15	108S	OWL	29.3	10.6	7.5	13/32	2183	35
TP39434000	P275/60R15	107S	OWL	28.0	11.0	8.0	11/32	2149	44
TP23863000	P295/50R15	108S	OWL	26.6	12.4	9.5	11/32	2205	44
TP41071000	P215/70R16	99S	OWL	28.0	9.0	6.5	12/32	1709	35
TP41029100	P225/70R16	102S	OWL	28.6	9.3	6.5	12/32	1819	35
TP41082900	P235/70R16	106S	OWL	29.1	9.7	7.0	12/32	2094	35
TP41101900	P245/70R16	106S	OWL	29.7	10.1	7.0	13/32	2094	35
TP41202100	P245/75R16	109S	OWL	30.6	9.8	7.0	13/32	2271	35
TP41022200	P255/70R16	111S	OWL	30.2	10.6	7.5	13/32	2403	35
TP41103500	P265/70R16	111S	OWL	30.8	11.0	8.0	13/32	2403	35
TP41152100	P265/75R16	114S	OWL	31.7	10.6	7.5	14/32	2601	35
TP50128600	P275/70R16	114S	OWL	31.2	11.0	8.0	13/32	2601	35
TP25715000	P225/65R17	102S	OWL	28.5	9.0	6.5	10/32	1874	44
TP42446100	P235/65R17	103S	OWL	29.0	9.6	7.0	12/32	1929	44
TP37100000	P245/65R17	105S	OWL	29.5	9.8	7.0	10/32	2039	44
TP41106500	P245/70R17	108S	OWL	30.7	10.1	7.0	13/32	2205	35
TP41491000	P255/65R17	110S	OWL	30.1	10.2	7.5	11/32	2337	44
TP41170000	P255/70R17	110S	OWL	31.1	10.6	7.5	13/32	2337	35
TP41293000	P265/65R17	112S	OWL	30.6	10.7	8.0	11/32	2469	44
TP41305200	P265/70R17	113S	OWL	31.7	10.9	8.0	13/32	2535	35
TP42411000	P275/60R17	110S	OWL	30.0	11.0	8.0	11/32	2337	44
TP42499000	P275/65R17	115T	OWL	31.1	10.9	8.0	11/32	2679	44
TP41120000	P265/60R18	109S	OWL	30.5	10.7	8.0	11/32	2271	44
TP42520000	P275/65R18	114S	OWL	32.1	11.0	8.0	10/32	2601	44
TP43207000	P285/60R18	114S	BSW	31.5	11.5	8.5	11/32	2601	44
TL38000000	LT235/80R17	120/117Q 10	OWL	31.7	9.1	6.5	15/32	S3085/D2835	80
TL18542300	31X10.50R15LT	109S 6C	OWL	30.3	10.9	8.5	15/32	2270	50



- Double steel-belted construction for long-lasting wear and uniformity
- Jointless spiral-wrapped full nylon cap for added strength and durability
- Rib-type tread design with deep shoulder grooves provides all-season capability
- Continuous shoulder ribs provide smooth, even tread wear and increased tread life
- Premium rubber compound and extra plies* resist cuts, punctures and abrasions
- Extra heavy-duty sidewall construction delivers responsive handling and performance under demanding commercial applications

Part #	Tire Size	Service Description / Ply Rating	Side wall	Overall Diameter (in)	Section Width (in)	Rim Width (in)	Tread Depth (in)	Max Load (lbs)	Max PSI
TL02362000	LT5.00R12	83/81P 8	BSW	22.4	5.5	3.5	11/32	S1070/D1025	65
TL02800000	LT5.50R12	92/90P 10	BSW	23.6	6.3	3.5	11/32	S1389/D1323	70
TL03682000	LT5.50R13	97/95P 12	BSW	24.7	6.3	3.5	11/32	S1610/D1521	90
TL12459000	LT205/80R14	109/107Q 8	BSW	27.1	8.3	6.0	12/32	S2271/D2149	65
TL16001200	LT235/75R15	110/107Q 8	BSW	28.9	9.6	6.5	14/32	S2335/D2150	65
TL30169000	LT215/85R16*	115/112Q 10	BSW	30.4	8.8	6.0	14/32	S2680/D2470	80
TL30158000	LT225/75R16	115/112Q 10	BSW	29.3	9.1	6.0	12/32	S2680/D2470	80
TL30186000	LT235/85R16*	120/116Q 10	BSW	31.7	9.6	6.5	15/32	S3042/D2778	80
TL30196000	LT245/75R16*	120/116Q 10	BSW	30.5	10.0	7.0	14/32	S3042/D2778	80
TL30218600	LT265/75R16*	123/120Q 10	BSW	31.7	10.8	7.5	14/32	S3415/D3085	80
TL00016100	LT235/80R17	120/117Q 10	BSW	31.7	9.0	6.5	14/32	S3085/D2835	80
TL00001100	LT245/70R17	119/116Q 10	BSW	30.7	9.7	7.0	14/32	S3000/D2755	65
TL00009100	LT265/70R17	121/118Q 10	BSW	31.7	10.7	8.0	14/32	S3195/D2910	65
TL00017100	145R12C	81/79P 6	BSW	21.3	5.7	4.0	10/32	S1019/D963	32
TL02352000	155/70R12C	104/102N	BSW	20.7	6.2	4.5	10/32	S1984/D1874	95
TL08002000	165R13C	94/93N 8	BSW	23.5	6.4	4.5	11/32	S1477/D1433	50
TL08694000	175R13C	97/95N 8	BSW	24.1	7.0	5.0	11/32	S1609/D1521	33
TL12413000	185R14C	102/100R 8	BSW	27.0	7.5	5.5	12/32	S1875/D1765	65
TL12452000	195R14C	106/104N 8	BSW	29.6	7.8	5.5	12/32	S2095/D1985	65
TL12468000	205/70R14C	102/100Q 8	BSW	25.4	8.3	6.0	14/32	S1874/D1764	55
TL12458000	205R14C	109/107Q 8	BSW	27.0	8.3	6.0	12/32	S2271/D2150	65
TL12470000	215/75R14C	112/110Q 8	BSW	26.7	8.8	6.0	12/32	S2469/D2337	70
TL12493000	185R15C	103/102Q 8	BSW	26.6	7.5	5.5	12/32	S1929/D1874	65
TL12510000	195R15C	106/104R 8	BSW	27.3	7.8	5.5	12/32	S2095/D985	65
TL12518000	205/70R15C	106/104R 8	BSW	26.3	8.1	6.0	14/32	S2095/D985	65
TL15800000	215/70R15C	109/107R 8	BSW	26.9	8.5	6.5	14/32	S2271/D2149	65
TL15821000	225/70R15C	112/110Q 8	BSW	27.4	9.1	6.5	14/32	S2469/D2337	65
TL22100000	175/75R16C	101/99R 8	BSW	26.3	7.1	5.0	12/32	S1819/D1708	70
TL22113000	185/75R16C	104/102R 8	BSW	27.0	7.4	5.0	12/32	S1984/D1874	70
TL22120000	195/75R16C	107/105R 8	BSW	27.5	7.9	5.5	12/32	S2149/D2039	70
TL22122000	195/75R16C	110/108N 10	BSW	27.5	7.9	5.5	12/32	S2335/D2205	75
TL22210000	205/75R16C	110/108R 8	BSW	28.1	8.1	5.5	12/32	S2335/D2205	70
TL22212000	205/75R16C	113/111R 10	BSW	28.1	8.2	5.5	12/32	S2535/D2405	75
TL22214000	215/75R16C	113/111R 8	BSW	28.7	8.8	6.0	12/32	S2535/D2403	70
TL22218000	225/75R16C	116/114Q 8	BSW	29.3	9.1	6.0	12/32	S2756/D2601	70
TL22219000	225/75R16C	121/120R 10	BSW	29.3	8.9	6.0	12/32	S3195/D3085	80

*3-ply sidewall

- Double steel-belted construction for long-lasting wear and uniformity
- Jointless spiral-wrapped full nylon cap for added strength and durability
- All-Season tread pattern delivers a smooth, quiet ride for light truck and sport utility vehicles
- Specially formulated rubber compound allows for exceptional handling in various road and weather conditions
- M&S All-season rated
- UTQG 420 A B (P-metric sizes only)



Part #	Tire Size	Service Description /Ply Rating	Side wall	Overall Diameter (in)	Section Width (in)	Rim Width (in)	Tread Depth (in)	Max Load (lbs)	Max PSI
TP27039000	P215/75R14	101S XL	OWL	26.8	8.7	6.0	14/32	1819	41
TP23920000	195/80R15	96S	BSW	27.3	7.8	5.5	13/32	1565	38
TP23910000	195R15	94S	BSW	27.3	7.8	5.5	13/32	1477	33
TP27023000	P215/75R15	102S XL	OWL	27.8	8.7	6.0	14/32	1874	41
TP39452400	215/80R15	102Q	RWL	28.4	8.7	6.0	14/32	1874	38
TP39450000	215R15	100Q	RWL	28.4	8.7	6.0	14/32	1760	33
TP27026000	P225/75R15	105S XL	OWL	28.4	9.1	6.0	14/32	2028	41
TP27028000	P235/75R15	108S XL	OWL	29.0	9.5	6.5	14/32	2183	41
TP41016000	P225/70R16	101S	OWL	28.6	9.2	6.5	14/32	1819	35
TP41080100	P235/70R16	106S	OWL	29.1	9.7	7.0	14/32	2094	36
TP41100400	P245/70R16	111S	OWL	29.7	9.8	7.0	14/32	2403	42
TP41020000	P255/70R16	109S	OWL	30.2	10.5	7.5	14/32	2271	35
TP41103600	P265/70R16	112S	OWL	30.8	11.0	8.0	14/32	2469	35
TP41106000	P275/70R16	114S	OWL	31.3	11.3	8.0	15/32	2601	35
TP41302200	P265/70R17	115S	OWL	31.8	10.8	8.0	14/32	2679	36
TP42498000	P275/65R17	115T	OWL	31.1	11.0	8.0	12/32	2679	41
TL12433000	185R14LT	102/100N 8	RWL	25.7	7.2	5.5	13/32	S1875/D1765	33
TL12494000	195R15LT	103/101Q 6	BSW	27.3	7.9	5.5	13/32	S1929/D1819	33
TL15904000	LT215/75R15	100/97S 6	BSW	27.7	8.5	6.0	14/32	S1765/D1610	50
TL16000000	LT235/75R15	104/101M 6	OWL	29.0	9.6	6.5	14/32	S1985/D1820	50
TL16002200	LT235/75R15	110/107Q 8	OWL	29.0	9.6	6.5	14/32	S2335/D2150	65
TL30166000	LT215/85R16	110/107S 8	BSW	30.4	8.9	6.0	14/32	S2335/D2150	65
TL30168000	LT215/85R16*	115/112Q 10	BSW	30.4	8.7	6.0	14/32	S2680/D2470	80
TL28100000	LT225/70R16	102/99Q 6	OWL	28.6	9.3	6.5	14/32	S1875/D1710	50
TL30170000	LT225/75R16	110/107S 8	OWL	29.4	9.1	6.0	14/32	S2335/D2150	65
TL30160000	LT225/75R16	115/112Q 10	OWL	29.4	9.1	6.0	14/32	S2680/D2470	80
TL28370000	LT235/70R16	104/101Q 6	OWL	29.1	9.7	7.0	14/32	S1985/D1820	50
TL30176000	LT235/85R16	114/111S 8	BSW	31.7	9.5	6.5	15/32	S2623/D2381	65
TL30180000	LT235/85R16*	120/116Q 10	BSW	31.7	9.6	6.5	15/32	S3042/D2778	80
TL28400000	LT245/70R16	106/103Q 6	OWL	29.7	9.8	7.0	14/32	S2095/D1930	50
TL30192000	LT245/75R16	108/104S 6	OWL	30.6	9.9	7.0	14/32	S2205/D2006	50
TL30191100	LT245/75R16	114/111S 8	OWL	30.6	9.9	7.0	14/32	S2623/D2381	65
TL30190000	LT245/75R16*	120/116Q 10	OWL	30.6	9.9	7.0	14/32	S3042/D2778	80
TL28380000	LT255/70R16	108/104Q 6	OWL	30.2	10.5	7.5	14/32	S2205/D1985	50
TL28600000	LT265/70R16	110/107Q 6	OWL	30.8	11.0	8.0	14/32	S2335/D2150	50
TL30210000	LT265/75R16	112/109S 6	OWL	31.8	10.7	7.5	15/32	S2470/D2270	50
TL30213000	LT265/75R16*	123/120M 10	OWL	31.8	10.7	7.5	15/32	S3415/D3085	80
TL28410000	LT275/70R16	112/109Q 6	OWL	31.3	11.3	8.0	15/32	S2470/D2270	50
TL30261000	LT285/75R16	116/113Q 6	OWL	33.0	11.7	8.0	15/32	S2755/D2535	50
TL30262000	LT285/75R16	122/119M 8	OWL	32.9	11.7	8.0	15/32	S3305/D3000	65
TL37304000	LT265/70R17	112/109Q 6	OWL	31.8	10.8	8.0	14/32	S2470/D2270	50
TL13806000	27X8.50R14LT	95S 6	OWL	26.3	8.9	7.0	15/32	1515	50
TL18520000	30X9.50R15LT	104S 6	OWL	29.3	9.8	7.5	15/32	1990	50
TL18530000	31X10.50R15LT	109S 6	OWL	30.3	10.9	8.5	15/32	2271	50
TL18550000	32X11.50R15LT	113S 6	OWL	31.3	11.6	9.0	15/32	2530	50
TL18560000	33X12.50R15LT	108S 6	OWL	32.2	12.7	10.0	15/32	2225	35
TL03004000	155R13C	91/89N 8	BSW	22.9	6.2	4.5	11/32	S1355/D1280	65
TL12428000	185R14C	102/100N 8	BSW	25.7	7.5	5.5	13/32	S1875/D1765	65
TL12498000	195R15C	106/104R 8	BSW	27.3	7.8	5.5	13/32	S2095/D1985	65
TL22201000	205R16C	110/108Q 8	BSW	28.9	8.3	6.0	13/32	S2337/D2205	65

*3-ply sidewall

BSW - Black Sidewall

OWL - Outline White Letter

OBL - Outline Black Letter

XL - Extra Load

Sizes may be limited by market.



- All-Season, All-Terrain tire designed with additional on-road refinements
- Aggressive tread pattern designed to provide good off-road traction while maintaining good noise performance
- Jointless spiral-wound cap ply maximizes ride refinement and durability
- Overall construction designed to improve lateral stability and handling on LT vehicles
- Pinned for studs
- UTQG 480 A B (P-metric sizes only)

Part #	Tire Size	Service Description / Ply Rating	Side wall	Overall Diameter (in)	Section Width (in)	Rim Width (in)	Tread Depth (in)	Max Load (lbs)	Max PSI
TP27037100	P215/75R14	101S	OWL	26.7	8.8	6.0	14/32	1819	35
TP39205200	P205/70R15	95S	OWL	26.5	8.2	6.0	11/32	1499	35
TP27054000	P225/75R15	105S XL	OWL	28.4	9.1	6.0	14/32	2028	41
TP27034400	P235/75R15	108S XL	OWL	29.0	9.6	6.5	14/32	2183	41
TP41018800	P225/70R16	101S	OWL	28.6	9.1	6.5	13/32	1819	35
TP41083500	P235/70R16	106S	OWL	29.1	9.6	7.0	13/32	2094	36
TP41101200	P245/70R16	111S	OWL	29.7	9.8	7.0	14/32	2403	42
TP41202600	P245/75R16	109S	OWL	30.6	10.0	7.0	14/32	2271	35
TP41029000	P255/70R16	109S	OWL	30.2	10.5	7.5	14/32	2271	35
TP41104400	P265/70R16	112S	OWL	30.8	10.8	8.0	15/32	2469	36
TP41154000	P265/75R16	114S	OWL	31.8	10.7	7.5	15/32	2601	35
TP41108100	P275/70R16	114S	OWL	31.3	11.0	8.0	14/32	2601	35
TP42446900	P235/65R17	103S	OWL	29.1	9.5	7.0	14/32	1929	44
TP41180000	P245/65R17	105S	OWL	29.4	9.8	7.0	14/32	2039	44
TP41290000	P265/65R17	112S	OWL	30.6	10.6	8.0	14/32	2469	44
TP41305600	P265/70R17	115S	OWL	31.7	10.8	8.0	15/32	2679	36
TL15924000	LT225/75R15	102/99Q 6	OWL	28.4	9.1	6.0	17/32	S1875/D1710	50
TL15922000	LT225/75R15*	108/104Q 8	OWL	28.4	9.1	6.0	17/32	S2205/D1985	65
TL16002600	LT235/75R15	104/101Q 6	OWL	29.0	9.6	6.5	16/32	S1985/D1820	50
TL30166600	LT215/85R16*	115/112Q 10	BSW	30.4	8.7	6.0	17/32	S2680/D2470	80
TL30170800	LT225/75R16*	115/112Q 10	OWL	29.4	9.1	6.0	17/32	S2680/D2470	80
TL28371000	LT235/70R16	104/101Q 6	OWL	29.1	9.6	7.0	14/32	S1985/D1820	50
TL30186400	LT235/85R16*	120/116Q 10	BSW	31.7	9.4	6.5	17/32	S3042/D2778	80
TL30202000	LT245/75R16	108/104S 6	OWL	30.6	9.9	7.0	15/32	S2205/D2006	50
TL30203000	LT245/75R16*	120/116Q 10	OWL	30.6	9.9	7.0	15/32	S3042/D2778	80
TL28381000	LT255/70R16	108/104Q 6	OWL	30.2	10.4	7.5	16/32	S2205/D1985	50
TL28390000	LT255/85R16*	119/116Q 8	BSW	33.0	10.2	7.0	17/32	S3000/D2755	65
TL28603000	LT265/70R16	110/107Q 6	OWL	30.8	10.8	8.0	16/32	S2335/D2150	50
TL30213200	LT265/75R16	112/109S 6	OWL	31.8	10.7	7.5	16/32	S2470/D2270	50
TL30213400	LT265/75R16*	123/120M 10	OWL	31.8	10.7	7.5	16/32	S3415/D3085	80
TL28415000	LT275/70R16	112/109Q 6	OWL	31.3	10.8	8.0	16/32	S2470/D2270	50
TL30270000	LT285/75R16*	122/119M 8	OWL	33.0	11.6	8.0	17/32	S3305/D3000	65
TL30272000	LT285/75R16*	126/123M 10	OWL	33.0	11.7	8.0	17/32	S3750/D3420	80
TL30294000	LT305/70R16*	118/115Q 8	OWL	33.0	12.4	9.0	17/32	S2910/D2680	50
TL30302000	LT315/75R16*	121Q 8	OWL	34.6	12.8	8.5	16/32	3195	50
TL37300000	LT245/70R17*	114/110S 8	OWL	30.7	9.8	7.0	16/32	S2600/D2335	65
TL43220000	LT255/65R17*	114/110S 8	OWL	30.1	10.2	7.5	14/32	S2600/D2335	65
TL37310000	LT265/70R17*	121/118Q 10	OWL	31.8	10.7	8.0	16/32	S3195/D2910	80
TL37605000	LT275/70R17	114/110S 6	OWL	32.4	11.1	8.0	16/32	S2600/D2335	50
TL37350000	LT285/70R17*	121/118Q 8	OWL	32.9	11.5	8.5	16/32	S3195/D2910	65
TL37503000	LT305/70R17*	119/116Q 8	OWL	34.0	12.4	9.0	17/32	S3000/D2755	50
TL37830000	LT275/65R18*	123/120Q 10	OWL	32.1	10.9	8.0	14/32	S3415/D3085	80
TL18526000	30X9.50R15LT	104S 6	OWL	29.3	9.8	7.5	16/32	1985	50
TL18544000	31X10.50R15LT	109S 6	OWL	30.3	10.8	8.5	16/32	2271	50
TL18556000	32X11.50R15LT	113S 6	OWL	31.3	11.6	9.0	17/32	2535	50
TL18564000	33X12.50R15LT	108S 6	OWL	32.3	12.7	10.0	17/32	2205	35
TL12516000	205/70R15C	106/104Q 8	BSW	26.5	8.2	6.0	13/32	S2095/D1985	65

*3-ply sidewall

BSW - Black Sidewall

OWL - Outline White Letter

OBL - Outline Black Letter

XL - Extra Load

Sizes may be limited by market.

- All-Season, All-Terrain tire designed for excellent off-road performance while retaining on-road refinement
- Multi-pitch tread pattern design minimizes pattern and road noise while maintaining excellent off-road performance
- Staggered shoulder lug design creates a biting edge for extra off-road traction
- 3D tread blocks provide additional stiffness to minimize irregular wear and increase overall stability
- Four unique U-shaped circumferential grooves offer excellent hydroplaning resistance while minimizing rock retention
- Jointless spiral-wound cap ply maximizes ride refinement and durability
- Overall construction designed to improve off-road stability and handling
- UTQG 500 A B (Metric sizes only)



Part #	Tire Size	Service Description / Ply Rating	Side wall	Overall Diameter (in)	Section Width (in)	Rim Width (in)	Tread Depth (in)	Max Load (lbs)	Max PSI
TP39206400	205/70R15	96T	OWL	26.3	8.2	6.0	13/32	1565	44
TP27017200	205/75R15	97T	OWL	27.1	8.0	5.5	13/32	1609	44
TP27022600	215/75R15*	100S	OWL	27.8	8.7	6.0	13/32	1754	44
TP25714000	225/70R15*	100S	OWL	27.4	9.0	6.5	12/32	1754	44
TP27049200	225/75R15*	102S	OWL	28.3	8.9	6.0	13/32	1874	44
TP27033300	235/75R15*	109S XL	OWL	28.9	9.5	6.5	12/32	2271	44
TP39235000	255/70R15	108T	OWL	29.1	10.2	7.5	13/32	2205	44
TP39240400	265/70R15*	112S	OWL	29.6	10.8	8.0	13/32	2469	44
TP40978600	215/65R16	98T	OWL	27.0	8.7	6.5	13/32	1653	44
TP41064400	215/70R16	100T	OWL	27.9	8.7	6.5	13/32	1764	44
TP41019100	225/75R16*	108S XL	OWL	29.3	8.9	6.0	15/32	2205	44
TP41015200	235/60R16	104H XL	BSW	27.1	9.5	7.0	13/32	1984	50
TP41080500	235/70R16	106T	OWL	29.0	9.4	7.0	13/32	2094	44
TP41083900	245/70R16	107T	OWL	29.5	9.8	7.0	13/32	2149	44
TP41225200	255/65R16	109T	OWL	29.0	10.2	7.5	13/32	2271	44
TP41021800	255/70R16	111T	OWL	30.0	10.2	7.5	13/32	2403	44
TP00022200	265/70R16*	112T	OWL	30.6	10.8	8.0	16/32	2469	44
TP25715800	225/65R17	102T	OWL	28.5	9.0	6.5	13/32	1874	44
TP42446800	235/65R17	104T	OWL	29.1	9.5	7.0	13/32	1984	44
TP37100600	245/65R17	107S	OWL	29.5	9.8	7.0	13/32	2149	44
TP41107200	245/70R17*	110S	OWL	30.7	9.6	7.0	13/32	2335	44
TP41492000	255/65R17	110H	BSW	30.1	10.2	7.5	13/32	2337	44
TP41171000	255/70R17*	112S	BSW	31.1	10.0	7.5	13/32	2469	44
TP41106400	265/65R17	112T	OWL	30.6	10.7	8.0	13/32	2469	44
TP41304400	265/70R17*	115S	OWL	31.8	10.8	8.0	13/32	2679	44
TP42498200	275/65R17	115T	OWL	31.1	11.0	8.0	13/32	2679	44
TP43118100	255/55R18*	109H XL	BSW	29.1	10.2	8.0	13/32	2270	44
TP43158300	255/60R18*	112H XL	BSW	30.0	10.0	7.5	13/32	2469	44
TP43186000	265/70R18*	116S	OWL	32.6	10.8	8.0	13/32	2755	44
TP42522000	275/65R18*	116S	BSW	32.1	11.0	8.0	16/32	2755	44
TP45418200	305/50R20*	120T XL	OWL	32.0	12.4	9.5	14/32	3042	44
TL16001900	LT235/75R15	104/101S 6	OWL	28.9	9.3	6.5	14/32	S1985/D1820	50
TL28101000	LT225/70R16	102/99S 6	OWL	28.4	9.0	6.5	16/32	S1875/D1710	50
TL30171800	LT225/75R16	115/112Q 10	OWL	29.3	8.8	6.0	14/32	S2680/D2470	80
TL30179000	LT235/85R16*	120/116S 10	OWL	31.7	9.6	6.5	15/32	S3042/D2778	80
TL30193300	LT245/75R16	108/104S 6	OWL	30.5	9.8	7.0	16/32	S2205/D2006	50
TL30191600	LT245/75R16	120/116Q 10	OWL	30.5	9.8	7.0	16/32	S3042/D2778	80
TL28605000	LT265/70R16	117/114S 8	OWL	30.6	10.7	8.0	16/32	S2835/D2600	65
TL30218800	LT265/75R16	119/116Q 8	OWL	31.7	10.5	7.5	16/32	S3000/D2755	65
TL30218900	LT265/75R16	123/120Q 10	OWL	31.7	10.5	7.5	16/32	S3415/D3085	80
TL30272300	LT285/75R16	122/119R 8	OWL	32.8	11.3	8.0	17/32	S3305/D3000	65
TL30272400	LT285/75R16	126/123Q 10	OWL	32.8	11.3	8.0	17/32	S3750/D3415	80
TL37108000	LT225/75R17*	116/113Q 10	OWL	30.3	8.9	6.0	15/32	S3042/D2540	80
TL37202200	LT235/80R17	120/117R 10	OWL	31.8	9.3	6.5	16/32	S3085/D2835	80
TL37309400	LT265/70R17	121/118R 10	OWL	31.7	10.7	8.0	16/32	S3195/D2910	80
TL37312000	LT285/70R17	121/118R 8	OWL	32.8	11.5	8.5	17/32	S3195/D2910	65
TL37505200	LT305/70R17*	119/116Q 8	OWL	34.0	12.4	9.0	17/32	S3000/D2755	65
TL37506000	LT315/70R17	121/118R 8	OWL	34.4	12.7	9.5	17/32	S3195/D2910	50
TL37620800	LT275/65R18	123/120S 10	OWL	32.1	11.0	8.0	16/32	S3415/D3085	80
TL37833000	LT285/65R18	125/122R 10	OWL	32.6	11.5	8.5	17/32	S3640/D3305	80
TL00062200	LT325/65R18	121/118S 8	OWL	34.6	13.0	9.5	17/32	S3195/D2910	50
TL00063200	LT305/55R20	121/118S 10	OWL	33.2	12.4	9.5	16/32	S3195/D2910	65
TL00032200	LT325/60R20	126/123S 10	OWL	35.4	13.0	9.5	16/32	S3750/D3415	65
TL18524200	30X9.50R15LT*	104S 6	OWL	30.0	9.5	7.5	16/32	1984	51
TL18565200	33X12.5R15LT	108S 6	OWL	33.0	12.5	10.0	17/32	2205	51
TL18573400	35X12.5R15LT*	113Q 6	OWL	35.0	12.5	10.0	17/32	2540	51
TL18542600	31X10.50R15LT*	109S 6	OWL	30.5	10.5	8.5	16/32	2270	50

BSW - Black Sidewall

OWL - Outline White Letter

OBL - Outline Black Letter

XL - Extra Load

*3-ply sidewall

Sizes may be limited by market.



- Double steel-belted construction for long-lasting wear and uniformity
- Jointless spiral-wrapped full nylon cap for added strength and durability
- Special tread design delivers excellent traction in both on and off-road terrain
- Open shoulder lugs provide exceptional self-cleaning capability
- Premium rubber compound and heavy-duty construction give excellent durability and strength
- Attractive rugged appearance available in outlined white letters or black serrated letters
- M&S All-season rated

Part #	Tire Size	Service Description / Ply Rating	Side wall	Overall Diameter (in)	Section Width (in)	Rim Width (in)	Tread Depth (in)	Max Load (lbs)	Max PSI
TL15705000	LT205/75R15	98/95Q 6	OWL	27.2	8.2	5.5	16/32	S1655/D1521	50
TL15902000	LT215/75R15	100/97M 6	OWL	27.8	8.7	6.0	16/32	S1765/D1610	50
TL16003000	LT235/75R15	104/101M 6	OWL	29.0	9.3	6.5	17/32	S1985/D1820	50
TL30169600	LT215/85R16*	115/112Q 10	BSW	30.4	8.8	6.0	17/32	S2680/D2470	80
TL30184000	LT235/85R16*	120/116Q 10	BSW	31.7	9.6	6.5	17/32	S3042/D2778	80
TL30194000	LT245/75R16*	120/116Q 10	OWL	30.6	9.8	7.0	17/32	S3042/D2778	80
TL30214000	LT265/75R16	112/109S 6	OWL	31.8	10.8	7.5	17/32	S2470/D2270	50
TL30215000	LT265/75R16	119/116Q 8	OWL	31.8	10.8	7.5	17/32	S3000/D2755	65
TL30215500	LT265/75R16*	123/120M 10	OWL	31.7	10.8	7.5	17/32	S3415/D3085	80
TL30264000	LT285/75R16	122/119M 8	OWL	32.9	11.7	8.0	17/32	S3305/D3000	65
TL30301000	LT315/75R16	121Q 8	OWL	34.6	12.8	8.5	18/32	3195	50
TL37301000	LT265/70R17	118/115Q 8	OWL	31.8	10.8	8.0	18/32	S2910/D2680	65
TL37502000	LT305/70R17	119/116N 8	OWL	34.0	12.4	9.0	18/32	S3000/D2755	50
TL18522000	30X9.50R15LT	104S 6	OWL	29.3	9.8	7.5	17/32	1990	50
TL18534000	31X10.50R15LT	109S 6	OWL	30.3	10.9	8.5	18/32	2271	50
TL18554000	32X11.50R15LT	113S 6	OWL	31.3	11.7	9.0	18/32	2530	50
TL12429200	185R14C	102/100R 8	BSW	25.5	7.4	5.5	16/32	S1875/D1765	65
TL12456800	195R14C	106/104R 8	BSW	26.1	7.8	5.5	17/32	S2090/D1980	65
TL22203000	205R16C	110/108Q 8	OWL	28.9	8.4	6.0	17/32	S2337/D2205	65

*3-ply sidewall

- Double steel-belted radial construction for long-lasting wear and uniformity
- Jointless spiral-wrapped full nylon cap for added strength and durability
- Extra strong, durable casing helps resist punctures and abrasions
- Premium rubber compound with tread siping delivers maximum control in various weather conditions
- Pinned for studs
- M&S All-season rated
- UTQG 380 AB (P-metric sizes only)



Part #	Tire Size	Service Description / Ply Rating	Sidewall	Overall Diameter (in)	Section Width (in)	Rim Width (in)	Tread Depth (in)	Max Load (lbs)	Max PSI
TP27033200	P235/75R15	105Q	OWL	29.0	9.5	6.5	14/32	2028	35
TL16006000	LT235/75R15	104/101Q 6	OWL	29.0	9.6	6.5	19/32	S1985/D1820	50
TL30177000	LT225/75R16	115/112Q 10	OWL	29.6	8.9	6.0	14/32	S2680/D2469	80
TL30185200	LT235/85R16*	120/116N 10	OBL	31.7	9.6	6.5	19/32	S3042/D2778	80
TL30197000	LT245/75R16	108/104N 6	OWL	30.6	10.0	7.0	20/32	S2205/D2006	50
TL30201000	LT245/75R16*	120/116N 10	OWL	30.6	10.0	7.0	20/32	S3042/D2778	80
TL30216000	LT265/75R16	112/109N 6	OWL	31.8	10.8	7.5	20/32	S2470/D2270	50
TL30216600	LT265/75R16	119/116Q 8	OWL	31.8	10.8	7.5	20/32	S3000/D2755	65
TL30216800	LT265/75R16	123/120M 10	OWL	31.8	10.7	7.5	20/32	S3415/D3086	80
TL28414000	LT275/70R16	112/109Q 6	OWL	31.8	10.8	8.0	20/32	S2470/D2270	50
TL30260000	LT285/75R16	122/119M 8	OWL	33.0	11.7	8.0	20/32	S3305/D3000	65
TL30290000	LT305/70R16	118/115Q 8	OWL	32.9	12.4	9.0	20/32	S2910/D2680	50
TL30300000	LT315/75R16	121Q 8	OWL	34.5	12.8	8.5	20/32	3195	50
TL37302000	LT265/70R17	112/109Q 6	OWL	31.8	10.9	8.0	20/32	S2470/D2270	50
TL37305000	LT265/70R17	119/116Q 8	OWL	31.8	10.9	8.0	20/32	S3000/D2755	65
TL37311000	LT285/70R17	121/118Q 8	OWL	33.0	11.4	8.5	20/32	S3195/D2910	65
TL37500000	LT305/70R17	119/116N 8	OWL	34.0	12.4	9.0	20/32	S3000/D2755	50
TL37800000	LT275/65R18	119/116Q 8	OWL	32.1	10.9	8.0	20/32	S3000/D2755	65
TL13808000	27X8.50R14LT	95Q 6	OWL	26.3	8.8	7.0	19/32	1520	50
TL18524000	30X9.50R15LT	104Q 6	OWL	29.3	9.8	7.5	19/32	1990	50
TL18538000	31X10.50R15LT	109Q 6	OWL	30.3	10.9	8.5	20/32	2271	50
TL18552000	32X11.50R15LT	113Q 6	OWL	31.3	11.6	9.0	20/32	2530	50
TL18562000	33X12.50R15LT	108Q 6	OWL	32.2	12.7	10.0	20/32	2225	35
TL18570000	35X12.50R15LT*	113Q 6	OWL	34.7	13.1	10.0	21/32	2535	35
TL12456900	195R14C	106/104R 8	OWL	26.0	7.9	5.5	17/32	S2095/D1984	65

*3-ply sidewall



- Staggered shoulder lugs for added traction on uneven terrain
- Deep tread blocks with large void-ratio tread pattern improves self-cleaning performance in the mud
- Heavy-duty sidewall construction enhances puncture resistance on rough terrain
- Shoulder tread blocks are pinned for studs for extra traction in winter weather
- Three body-ply construction in select sizes
- M&S All-season rated

Part #	Tire Size	Service Description / Ply Rating	Side wall	Overall Diameter (in)	Section Width (in)	Rim Width (in)	Tread Depth (in)	Max Load (lbs)	Max PSI
TL16009000	LT235/75R15	104/101Q 6	OWL	29.0	9.4	6.5	19/32	S1985/D1820	50
TL30186600	LT235/85R16*	120/116N 10	BSW	31.7	9.6	6.5	19/32	S3042/D2778	80
TL30205200	LT245/75R16*	120/116N 10	OWL	30.6	9.8	7.0	19/32	S3040/D2780	80
TL28394000	LT255/85R16	119/116N 8	BSW	33.3	10.3	7.0	19/32	S3000/D2755	65
TL30212900	LT265/75R16	112/109Q 6	OWL	31.8	10.8	7.5	19/32	S2470/D2270	50
TL30212400	LT265/75R16	119/116Q 8	OWL	31.8	10.8	7.5	19/32	S3000/D2755	65
TL30212100	LT265/75R16*	123/120M 10	OWL	31.8	10.6	7.5	19/32	S3415/D3085	80
TL28415400	LT275/70R16	112/109Q 6	OWL	31.3	11.1	8.0	19/32	S2470/D2270	50
TL30268000	LT285/75R16	122/119M 8	OWL	33.0	11.6	8.0	19/32	S3305/D3000	65
TL30291000	LT305/70R16	118/115Q 8	OWL	33.0	12.4	9.0	19/32	S2910/D2680	50
TL30303000	LT315/75R16	121Q 8	OWL	34.6	12.8	8.5	19/32	3195	50
TL00028100	LT235/80R17	120/117Q 10	OWL	31.8	9.3	6.5	19/32	S3086/D2833	80
TL37200200	LT245/70R17	114/110Q 8	OWL	30.8	9.7	7.0	19/32	S2600/D2335	65
TL37200400	LT245/70R17	119/116Q 10	OWL	30.8	9.7	7.0	19/32	S3000/D2756	80
TL00005100	LT255/65R17	114/110Q 8	OWL	30.2	10.3	7.5	20/32	S2600/D2335	65
TL37309000	LT265/70R17	118/115Q 8	OWL	31.8	10.8	8.0	19/32	S2910/D2680	65
TL37309200	LT265/70R17*	121/118Q 10	OWL	31.8	10.8	8.0	19/32	S3195/D2910	80
TL37604000	LT275/70R17	120/117Q 8	OWL	32.2	11.1	8.0	19/32	S3082/D2835	65
TL37600200	LT285/70R17	121/118Q 8	OWL	33.0	11.7	8.5	19/32	S3195/D2910	65
TL37505000	LT305/70R17	119/116N 8	OWL	34.0	12.2	9.0	21/32	S3000/D2755	50
TL37620200	LT275/65R18	119/116Q 8	OWL	32.1	11.0	8.0	20/32	S3000/D2755	65
TL37622000	LT275/70R18*	125/122Q 10	OWL	33.4	11.1	8.0	19/32	S3640/D3305	80
TL00064100	LT285/75R18	129/126Q 10	OWL	35.1	11.3	8.0	19/32	S4080/D3750	80
TL00062100	LT325/65R18	127/124Q 10	OWL	34.8	13.0	9.5	21/32	S3860/D3525	50
TL00058100	LT275/65R20	126/123Q 10	OWL	34.3	11.0	8.0	20/32	S3750/D3420	80
TL00063100	LT305/55R20	121/118Q 10	BSW	33.5	12.5	9.5	19/32	S3200/D2910	65
TL00032100	LT325/60R20	121/118Q 8	BSW	35.6	13.6	9.5	21/32	S3200/D2910	50
TL13804000	27X8.50R14LT	95Q 6	OWL	26.3	8.8	7.0	19/32	1520	50
TL18528000	30X9.50R15LT	104Q 6	OWL	29.9	9.7	7.5	20/32	1985	50
TL18529400	31X10.50R15LT	109Q 6	OWL	30.6	11.0	8.5	21/32	2270	50
TL18557000	32X11.50R15LT	113Q 6	OWL	31.9	11.6	9.0	21/32	2535	50
TL18565000	33X12.50R15LT	108Q 6	OWL	32.9	12.7	10.0	21/32	2205	35
TL18573000	35X12.50R15LT*	113Q 6	OWL	34.6	13.0	10.0	21/32	2535	35
TL00010100	35X12.50R17LT*	119Q 8	OWL	35.0	12.7	10.0	21/32	3000	50

*3-ply sidewall

- Aggressive, directional tread design provides excellent dry and wet handling stability on all types of terrain
- Multi-curve tread siping improves traction on loose dirt while enhancing braking and driving performance
- Unique tread element arrangement ensures a uniform tread contact area for sure-footed handling
- Multi-stage staggered shoulder pattern provides improved control even on the most difficult off-road and rocky terrain
- Nylon belt-reinforced tire construction improves puncture resistance and prolongs tread life



Radial

Part #	Tire Size	Service Description /Ply Rating	Side wall	Overall Diameter (in)	Section Width (in)	Rim Width (in)	Tread Depth (in)	Max Load (lbs)	Max PSI
TL16009200	LT235/75R15	104/101Q 6	BSW	29.0	9.4	6.5	19/32	S1985/D1820	50
TL22204000	205/70R15C	104/102R 6	BSW	26.4	8.3	6.0	16/32	S1985/D1875	55
TL22205000	205R16C	110/108Q 8	BSW	28.9	8.1	6.0	17/32	S2337/D2205	65
TL18527000	30X9.50R15LT	104Q 6	BSW	29.9	9.8	7.5	20/32	1985	50
TL18533800	31X10.50R15LT	109Q 6	BSW	30.6	10.8	8.5	20/32	2270	50
TL18578000	35X12.50R15LT	113Q 6	BSW	34.6	13.1	10.0	21/32	2535	35
TL30007600	35X12.50R16LT	121Q 8	BSW	34.6	13.0	10.0	21/32	3195	50
TL30026000	37X12.50R17LT	124Q 8	BSW	36.9	13.0	10.0	21/32	3525	50
TLO0007100	40X13.50R17LT	121Q 6	BSW	39.8	14.2	11.0	21/32	3195	35
TLO0061100	33X13.00R18LT	124Q 10	BSW	33.6	13.0	9.5	21/32	3525	65
TLO0057100	35X13.00R18LT	127Q 10	BSW	34.6	13.1	9.5	21/32	3858	65
TLO0008100	40X13.50R18LT	129Q 8	BSW	39.8	14.0	11.0	21/32	4080	50
TLO0059100	33X12.00R20LT	121Q 10	BSW	33.1	12.2	9.5	21/32	3200	65
TLO0031100	35X13.00R20LT	121Q 8	BSW	35.0	13.6	9.5	21/32	3200	50
TLO0075100	40X15.50R22LT	127Q 8	BSW	39.8	15.4	12.0	21/32	3860	50

- Heavy-duty bias ply construction for excellent durability and tread flexibility
- Multi-curve tread siping improves traction on loose dirt and slippery terrain
- Unique tread element arrangement ensures a uniform tread contact area for maximum road contact
- Aggressive side lug design provides improved side-bite on difficult off-road and rocky terrain
- Nylon belt-reinforced tire construction improves puncture resistance and durability



Bias

(engineered for competition only)

Part #	Tire Size	Service Description /Ply Rating	Side wall	Overall Diameter (in)	Section Width (in)	Rim Width (in)	Tread Depth (in)	Max Load (lbs)	Max PSI
TL30024700	37X12.50-16LT	124L 8	BSW	37.0	13.4	10.0	23/32	3525	45
TL30025900	37X12.50-17LT	124L 10	BSW	37.0	13.2	10.0	23/32	3525	45
TLO0007200	40X13.50-17LT	123L 8	BSW	40.1	14.3	11.0	23/32	3420	45



- Heavy-duty bias construction provides lasting performance
- Rugged tread pattern provides agile and controlled steering for competition rock crawling
- Unique multi-edged knob design and arrangement of sipes enhance traction on rock surfaces
- Large shoulder lugs provide unparalleled traction in snow and mud conditions
- Innovative tread pattern provides uniform contact patch for increased performance
- DOT-approved

Part #	Tire Size	Service Description / Ply Rating	Side wall	Overall Diameter (in)	Section Width (in)	Rim Width (in)	Tread Depth (in)	Max Load (lbs)	Max PSI
TL28398000	255/85-16LT	104L 8	BSW	33.5	10.0	7.0	23/32	2470	45
TL30006200	35X12.50-15LT	113L 6	BSW	35.0	13.5	10.0	27/32	2535	30
TL30007800	37X12.50-15LT	117L 8	BSW	37.1	13.3	10.0	27/32	2833	45
TL30008000	37X14.50-15LT	127L 8	BSW	37.1	15.3	12.0	27/32	3860	45
TL30009000	38X13.00-15LT	128L 8	BSW	38.2	13.3	10.0	27/32	3970	45
TL30007200	35X12.50-16LT	112L 6	BSW	35.0	13.1	10.0	27/32	2470	30
TL30008200	37X12.50-16LT	124L 8	BSW	36.8	13.4	10.0	27/32	3525	45
TL30008300	37X14.50-16LT	126L 8	BSW	37.0	14.5	12.0	27/32	3750	45
TL30009200	38.5X14.50-16LT	129L 8	BSW	38.8	15.3	12.0	27/32	4080	45
TL23690000	6.50-16LT	100L 6	BSW	30.0	7.9	5.5	19/32	1760	45
TL23691500	7.00-16LT	109L 8	BSW	31.0	8.5	5.5	20/32	2270	45
TL30035000	40X13.50-17LT	123L 8	BSW	40.0	14.0	11.0	27/32	3417	45

Creepy Crawler (engineered for competition only)

Part #	Tire Size	Service Description / Ply Rating	Side wall	Overall Diameter (in)	Section Width (in)	Rim Width (in)	Tread Depth (in)	Max Load (lbs)	Max PSI
TL30035200	40X13.50-17LT	123L 8	BSW	40.0	14.0	11.0	27/32	3417	45



MAXXIS

ST RADIAL