



- Advanced tread compound designed to decrease rolling resistance for improved fuel economy and tread life
- Double steel-belted construction for added strength and vehicle towing stability
- Excellent shock absorption while providing superior load handling performance

Part #	Tire Size	Service Description / Ply Rating	Side wall	Overall Diameter (in)	Section Width (in)	Rim Width (in)	Tread Depth (in)	Max Load (lbs)	Max PSI
TL08698000	ST175/80R13	4	BSW	24.1	7.1	5.0	9/32	1100	35
TL08696000	ST175/80R13	6	BSW	24.1	7.1	5.0	9/32	1360	50
TL08896000	ST185/80R13	6	BSW	24.7	7.4	5.0	9/32	1480	50
TL12462000	ST205/75R14	4	BSW	26.1	8.1	5.5	9/32	1430	35
TL12460000	ST205/75R14	6	BSW	26.1	8.1	5.5	9/32	1760	50
TL12461000	ST205/75R14	6	OWL	26.1	8.1	5.5	9/32	1760	50
TL12474000	ST215/75R14	6	BSW	26.7	8.6	6.0	9/32	1870	50
TL12475000	ST215/75R14	6	OWL	26.7	8.6	6.0	9/32	1870	50
TL15700000	ST205/75R15	6	BSW	27.1	8.1	5.5	9/32	1820	50
TL15701000	ST205/75R15	6	OWL	27.1	8.1	5.5	9/32	1820	50
TL15703000	ST205/75R15	8	BSW	27.1	8.1	5.5	9/32	2145	50
TL15712000	ST225/75R15	6	BSW	28.3	8.9	6.0	9/32	2150	50
TL15710000	ST225/75R15	8	BSW	28.3	8.9	6.0	9/32	2540	65
TL15711000	ST225/75R15	8	OWL	28.3	8.9	6.0	9/32	2540	65
TL15713000	ST225/75R15	10	BSW	28.3	8.9	6.0	9/32	2830	80
TL30140000	ST235/80R16	8	BSW	30.8	9.5	6.5	9/32	3000	65
TL30141000	ST235/80R16	10	BSW	30.8	9.5	6.5	9/32	3420	80

- Advanced tread compound formulation for ice and snow conditions
- Special shoulder design for snow in straight and lateral traction
- Saw-toothed block and high-density sipes arrangement improve grip in snow
- Central saw-toothed groove and rib for improved stability
- Jointless spiral-wrapped nylon cap provides tire uniformity and stability
- Random pitch arrangement for low noise
- M&S All-season rated and mountain/snowflake symbol certification



Part #	Tire Size	Service Description /Ply Rating	Side wall	Overall Diameter (in)	Section Width (in)	Rim Width (in)	Tread Depth (in)	Max Load (lbs)	Max PSI
TP09984000	155/65R13	73Q	BSW	21.0	6.1	4.5	11/32	805	44
TP10015400	155/70R13	75Q	BSW	21.6	6.2	4.5	11/32	853	44
TP12401600	165/70R13	79Q	BSW	22.1	6.7	5.0	11/32	963	44
TP20542600	175/70R13	82Q	BSW	22.7	7.0	5.0	12/32	1047	44
TP14677000	155/65R14	79Q XL	BSW	22.0	6.1	4.5	12/32	963	50
TP15729000	175/65R14	82Q	BSW	23.1	6.9	5.0	12/32	1047	44
TP16028800	185/60R14	82Q	BSW	22.7	7.4	5.5	12/32	1047	44
TP17635600	185/65R14	86Q	BSW	23.4	7.4	5.5	12/32	1168	44
TP23574600	185/70R14	88Q	BSW	24.3	7.4	5.5	12/32	1235	44
TP18299700	175/65R15	88Q	BSW	24.0	7.0	5.0	12/32	1235	50
TP18258200	185/55R15	86Q XL	BSW	23.0	7.6	6.0	12/32	1168	50
TP18308200	185/65R15	88Q	BSW	24.5	7.4	5.5	12/32	1235	44
TP23852200	195/55R15	85Q	BSW	23.4	7.9	6.0	12/32	1135	44
TP38014400	195/60R15	88Q	BSW	24.2	7.9	6.0	12/32	1235	44
TP23977400	195/65R15	91Q	BSW	25.0	7.9	6.0	12/32	1356	36
TP38061800	205/60R15	91Q	BSW	24.7	8.2	6.0	13/32	1356	44
TP15773000	205/65R15	94Q	BSW	25.5	8.2	6.0	13/32	1477	36
TP39609400	195/55R16	87Q	BSW	24.4	7.9	6.0	12/32	1356	50
TP39652600	195/60R16	89Q	BSW	25.3	7.9	6.0	12/32	1279	44
TP39707900	205/55R16	91Q	BSW	24.9	8.4	6.5	13/32	1356	44
TP40948800	205/60R16	96Q XL	BSW	25.6	8.2	6.0	13/32	1565	50
TP40948600	205/60R16	92Q	BSW	25.7	8.2	6.0	13/32	1389	44
TP40908500	215/55R16	93Q	BSW	25.3	8.8	7.0	13/32	1433	44
TP40906600	215/60R16	95Q	BSW	26.2	8.7	6.5	13/32	1521	44
TP41007400	225/60R16	98Q	BSW	26.6	9.0	6.5	13/32	1653	44
TP42408900	215/55R17	98Q XL	BSW	26.4	8.9	7.0	13/32	1653	50